

# PR-15 Spot Cleaner

## **Effective Cleaner**

Priorsvej 36 DK-8600 Silkeborg Tlf.: +45 86 82 64 44 E-mail: info@itw-spraytec.dk www.itw-spraytec.dk

#### **Description:**

Kema PR-15 can effectively dissolve most paints, varnishes, inks, asphalt and adhesive residues. Is ideal for the removal of graffiti. Can be used on a variety of surfaces such as glass, laminate, stone, concrete, metal etc. Loosens grease, resins and tar. The product can be applied to vertical surfaces to remove stubborn gasket remnants and sealants.

**Note:** A compatibility test should always be carried out before use, as PR-15 can affect certain plastics and rubbers, as well as painted and lacquered surfaces

#### **Properties:**

- Gasket Remover
- Graffiti and paint strippers
- Loosens hardened adhesive
- pH neutral
- Can easily be removed with water
- Biodegradable
- NSF A1 registered under 154571



**Application:** Apply PR-15 and allow time for the product to penetrate into heavier contamination, labels and adhesives. Dry with a cloth or rinse off with water. The cleaning operation may be enhanced by working the solvent into the surface using a brush. Treatment may be repeated. When dealing with very difficult to remove dirt and grime, the penetration time should be extended maximum 20 minutes.

### **Technical data:**

Part number 14145

Packing 500 ml Aerosol

Content 400 ml

Weight 345 g

Color Clear

Propellant CO2

Flash point <21°C

Soluble in Partly miscible with water

pH value app. 7

Information: Additional technical information or SDS can be downloaded from www.itw-spraytec.dk or please contact our customer service at: +45 86 82